

QTY.	PART NUMBER	SIZE		A (INI)	D (INI)	EFFECTIVE	SPRING RATE	WEIGHT	NOTES
		(IN)	(MM)	A (IN)	B (IN)	AREA (IN²)	(lbs/in)	WEIGHT	NOTES
	120-075-4	3/4"	20	13-3/8	3	1.5	81	8	
	120-10-4	1"	25	13-3/8	3	2.1	88	9	
	120-12-4	1-1/4"	32	13-7/8	3	3.3	75	12	
	120-15-4	1-1/2"	38	15-1/4	3-1/2	4.3	121	14	
	120-20-4	2''	50	15-1/4	4	6.3	143	18	
	120-25-4	2-1/2"	65	16-5/8	5	8.8	187	29	
	120-30-4	3"	80	16-5/8	5-1/2	13.1	230	34	
	120-40-4	4''	100	17	6-5/8	20.8	484	47	

THIS EXPANSION JOINT IS DESIGNED FOR AXIAL MOVEMENT ONLY. PIPES MUST BE PROPERLY GUIDED AND ANCHORED PER THE RECOMMENDATIONS OF THE EXPANSION JOINT MANUFACTURERS ASSOCIATION.

750°F (399°C)			
175 PSI (1206 kPa)			
250 PSI (1809 kPa)			
2" (50mm)			
1/2" (13mm)			

NOTES:

NSF 372 - LEAD FREE: The wetted surface of this product contacted by water contains less than one quarter of one percent (0.25%) of lead by weight. Material complies with state codes and standards where applicable, requiring reduced lead content.

